

## H6A-2 Smart Interactive Flat Panel



### Product Description

**4G+32G**  
Storage



**A55 \*8**  
GK6760V100 Chipset



**Android 14**






**Gather. Present. Brainstorm. Annotate. Educate. Stream.**  
All-in-one with H6A-2

### Features

- Multiple Sizes
- 4K UHD display
- Support up to 20 touch points
- Super narrow frame design
- 2 stylus magnetic slot
- convenient storage
- GK6760V100 Chipset
- Smart whiteboard touch writing
- Remote meeting
- Wireless transmission
- Multi-screen interaction
- Support internet sharing
- Low optical parallax writing
- Wider viewing angle

## Product Specifications

Model	55 inch	65 inch	75 inch	86 inch	98 inch
<b>LED Panel/Touch Parameters/Camera</b>					
Display Area	1210(H)×680(V)	1429(H)×804(V)	1649(H)×928(V)	1895(H)×1066(V)	2158(H)×1214(V)
Aspect	16:9				
Resolution	3840×2160 Pixels				
Backlight	D-LED				
Response Time	8ms				
Refreshing Frequency	60Hz				
Display Color	1.07B (10bit)				
Central point brightness	≥260cd/m <sup>2</sup>	≥350cd/m <sup>2</sup>	≥410cd/m <sup>2</sup>	≥450cd/m <sup>2</sup>	≥450cd/m <sup>2</sup>
Contrast Ratio	Base on the OC				
Viewing Angle	178(H/V)				
<b>Touch Parameters</b>					
Sensing Type	Infrared recognition				
System	Windows10/Windows8/Windows7/WindowsXP Android/Linux/MacOSX/Chrome				
Touch point	20 points touch				
Writing height	3mm				
Response Time	<15ms				
Touch Tool	Fingers, touch pens and other opaque objects				
Accuracy	±1mm(over 90%Area)				
Surface Hardness	Toughened Glass with Level 7 of Mohs Standard				
Output Coordinate	32767×32767				
<b>Android System Parameters</b>					
System Version	Android 14				
Chipset	Gk6760 V100				
CPU	Cortex-A55 *8				
GPU	Mali-G52 MP4				
RAM/ROM	4GB/32GB (Optional 8GB/128GB )				
<b>Android AIO interfaces</b>					
FRONT	USB 2.0 : 2				
REAR	WIFI 5G(Antenna): 1 WIFI 2.4G(Antenna): 1 TF CARD : 1 USB 2.0 : 1 USB3.0 : 1 TOUCH USB : 1				
	HDMI IN : 2 VGA : 1 VGAAUDIO IN : 1				
BOTTOM(75"/86"/98")	Rs232 : 1 LINE OUT : 1 COAX : 1 RJ45 IN : 1				
<b>General Parameters</b>					
Power Supply	100-240V~50/60Hz				
Overall Power	118W	186.7W	246.8W	353W	415W
Standby Power	≤0.5W				
Speaker Type	Two-channel				
Output Power	2×10W(full frequency)				
<b>Accessories</b>					
Accessories list (Optional)					
	OPS	Wireless transmitter	Mobile Stand		

## Packing information

Size	Display size (inch/mm)	Overall size/Weight W×D×H(mm)/kg	Packing size/Weight W×D×H(mm)/kg	QTY of containers(pcs) 20'GP/40'GP/40'HQ
55"	1210×680	1258×744×80/21.8	1360×165×885/27.6	116/226/357
65"	1429×804	1485×888×88/36.3	1630×160×1024/48	96/206/206
75"	1649×928	1707×1013×88/50.6	1855×160×1155/65.75	90/180/186
86"	1895×1066	1953×1152×88/65.1	2095×160×1288/82	38/80/160
98"	2158×1214	2216×1304×110/90	2355×160×1441/111	28/70/70